

Decoration Street LED MSL-LTD-ML- Specifications





About Us,

MSL USA's LED streetlights are trusted by electrical contractors, government agencies, and project managers across the United States.

Our selection of streetlights include fixtures with dusk to dawn photocell technology as well as weather resistant coating to ensure smooth operation through harsh weather conditions. We also offer solar powered streetlights for environmentally friendly projects. We advanced production technology, we deliver smart lighting solutions for streets, gardens, residential areas, and many more...



MSL-LTD-ML





MSL-LTD-ML is cutting-edge lighting solution is meticulously designed to withstand the test of time, minimizing maintenance and replacement costs while delivering consistent, high-quality illumination year after year. Built with premium-grade materials, this LED streetlight is engineered to handle a wide range of environmental conditions, from extreme heat to heavy rain and strong winds. Its weatherproof and corrosion-resistant design ensures unwavering performance even in the most challenging outdoor settings, making it ideal for streets, highways, parking lots, and public places.




SPECIFICATIONS


| Model | MSL-LTD-ML-30W | MSL-LTD-ML-50W | MSL-LTD-ML-80W | MSL-LTD-ML-100W | MSL-LTD-ML-150W | | | |
|-----------------------|---|----------------|--|-----------------|-----------------|--|--|--|
| | | | | | | | | |
| Led power | 30W | 50W | 80W | 100W | 150W | | | |
| Luminous flux | 5,100LM | 8,100LM | 12,400LM | 15,000LM | 21,000LM | | | |
| Voltage | | | 120-277VAC 120-347VAC 200-480VAC | | | | | |
| Fixture color | | | Black | | | | | |
| Color temperature | | | 3,000K-5,700K | | | | | |
| Distribution Type | | | Type II, III, IV, V | | | | | |
| Color rendering index | | | CRI <u>>80</u> | | | | | |
| PF | | | <u>></u> 0.9 | | | | | |
| Body Material | | High-duty d | lie-casting aluminum all | oy housing | | | | |
| IP Rating | | | IP65 | | | | | |
| Certificates | EN61347-1, EN61347-2-13, EN60598-2-1, EN60598-1 | | | | | | | |
| | UL 924, UL 1598, CAN/CSA -C.22.2 NO. 250.0, DLC, ETL/cETL listed, ENEC, CB, CE/RoHS | | | | | | | |
| Pole Diameter | 76MM/ 3" | | | | | | | |
| Warranty | | | 5 years | | | | | |



FIXTURE DIMENSIONS




DISTRIBUTION DIAGRAM



INSTALLATION OPTIONS

Depending on the type of light, you may need to have the right mounting-option available too. You can also buy Tenon Adaptor, Bullhorns and Spoke from us, suitable for wooden, metallic, or concrete poles - square or round.





Uses and Applications Guide

Streets Lighting Parking Lots Residential Roads Public Parks Gardens Pathways Bike Lanes

Ordering Guide

| Model | Voltage | LED Wattage | LED Color Temp | LED body color | Options | Options |
|------------|--|-----------------------------------|--------------------------|----------------|--------------------------------------|--|
| MSL-LTD-ML | AC120-277V AC120-347VAC AC200-480VAC | 30W 50W 80W 100W 150W | 30K 40K 50K 57K | BLK- Black | 00- 0-10VDC Dimming 01- Photocell | 6KV Surge protector *10KV Surge protector *20KV Surge protector *Customize up on request |